



POSEIDON LED



REDUCED ENVIRONMENTAL IMPACT



OPTIMAL BATTERY CHARGE



EFFICIENCY GREATER THAN 90%



INCREASED BATTERY LIFE



COMPACT CHARGER WITH SEVEN LED CONTROL BOARD FOR EFFICIENT CHARGER

POSEIDON offers a range of extremely compact and handy chargers, equipped with microprocessor control with 7 LED display, which allows a simple representation of the state of is an intuitive and robust charger with a high charging efficiency of 85%.

BATTERY CHARGE
Innovation

Ideal for:



MATERIAL HANDLING



FLOOR CARE MACHINES



GOLF CAR AND CLUB CAR



POSEIDON LED

TECHNICAL SPECIFICATIONS

www.estpower.net

FEATURES

- Display of charge status with 7 LEDs
- Very high efficiency over 85% and Power factor of 0.80 allow low energy consumption
- ON/OFF switch for enable or disable the charge
- External push button for programmable equalizing and weekend charge
- Quick test for charger functional verification
- Proportional charge function for shallow discharges
- Maximum and minimum voltage control before charging starts
- Maximum voltage control in charge
- Final charging time that can be set to adapt the charge cycle to battery conditions
- AutoStart with programmable delay
- Serial interface for highly precise programming and calibration
- Short circuit and reverse polarity protection
- Design, testing and production of transformers carried out internally
- Thermal protection on the power transformer to avoid over-temperature
- IP20 intrusion protection
- Conformal coating on the control card for moisture protection to grant high reliability
- Excellent ventilation system for better cooling of the transformer
- Working temperature 0 - 40°C



Volt	Amp.	Mod. 1Ph 230Vac	Mod. 1ph 240Vac	Capacity C5 Ah (9-11h)		Cabinet
Vdc	Adc	Vac	Vac	Min	Max	Type
12	15	•	•	85	100	S
12	20	•	•	110	135	S
12	25	•	•	135	165	S
12	30	•	•	165	200	S
12	40	•	•	220	265	S
12	50	•	•	270	330	N
12	60	•	•	325	400	N
24	15	•	•	85	100	S
24	20	•	•	110	135	S
24	25	•	•	135	165	S
24	30	•	•	165	200	S
24	40	•	•	220	265	S
24	50	•	•	270	330	N
24	60	•	•	325	400	N
24	80	•	•	435	530	N
36	20	•	•	110	135	S
36	25	•	•	135	165	S
36	30	•	•	165	200	S
36	40	•	•	220	265	N
36	50	•	•	270	330	N
36	60	•	•	325	400	N
48	20	•	•	110	135	S
48	25	•	•	135	165	N
48	30	•	•	165	200	N
48	40	•	•	220	265	N

• Model Available – Model not available

DIMENSION

S: 330x233x213 (LxWxH) mm
N: 425x272x266 (LxWxH) mm

CERTIFICATIONS

CE compliance
Safety: CEI EN60335-1
EMC: CEI EN61000-6-2
CEI EN61000-6-3
CEI EN62233

WARRANTY

12 months

MODELS

Any other models available on demand for different Battery Voltage, Current and Mains Supply.

Data subject to change without notice. All stated trademarks belong to their respective owners, any unauthorized use will be prosecuted according to the law.
POSEIDON LED - ENG Rev.01 22

Energy Systems Transnational Pte

Ltd69C, Tuas South Avenue 1, Singapore 637500

Tel: (65) 6262 6286 Fax: (65) 6262 6936

Email: sales@estpower.net

